

PRODUCT PARAMETERS



ITEM	IT-SL380	IT-SL1500	IT-SL18250
Nominal Power	30W-80W	100W-150W	180W-250W
Input Voltage	100-277VAC,50/60Hz	100-277VAC,50/60Hz	100-277VAC,50/60Hz
Power Factor	>0.95	>0.95	>0.95
THD	<15%	<15%	<15%
Light Distribution	II,III,IV	II,III,IV	II,III,IV
CCT	2700K~6500K	2700K~6500K	2700K~6500K
CRI	Ra>70	Ra>70	Ra>70
Dimensions	566*205*110mm	658*251*112mm	731*301*114mm
Protection Grade	IP66,IK09	IP66,IK09	IP66,IK09
LED	Lumileds 3030 or 5050	Lumileds 3030 or 5050	Lumileds 3030 or 5050
Electrical Protection	CLASS I or CLASS II	CLASS I or CLASS II	CLASS I or CLASS II
Luminous Flux	130~140Lm/W (3030 LED) 150~165Lm/W (5050 LED)	130~140Lm/W (3030 LED) 150~165Lm/W (5050 LED)	130~140Lm/W (3030 LED) 150~165Lm/W (5050 LED)
Package Size	596*225*130mm	688*271*132mm	761*321*134mm
Housing	Die-casting Aluminum	Die-casting Aluminum	Die-casting Aluminum
Warranty	≥5 Years	≥5 Years	≥5 Years

LIGHT DISTRIBUTION

