

can provide 7-10 years warranty

DURA ST



FEATURES

- Input voltage: 220V~240V / Universal input
- Lumen Maintenance: L90 @ 60,000 hours
- Working Temperature: -25°C ~ 50°C
- Storage Temperature: -25°C ~ 80°C
- Power Factor: >0.95 at Full Load

MATERIALS

- Casing material: Die-Cast Aluminum ADC12, Powder-Coated Finishing
- Cover: Tempered Glass
- Driver: Dimmable, Programmable & DALI Compatible 1~10V (Optional)
- NEMA Socket: Support NEMA, ZIGBEE, PLC, LORA Smart Lighting System (Optional)



Specification

Model No.	Power	Input current	Weight	Size	CCT	Efficacy	Lumen
OLE Dura ST90	90W	0.39A	10kg	400 x 565mm	<3500K	142 lm/W	12780 lm
					4000K	148 lm/W	13320 lm
					5000K	152 lm/W	13680 lm
					6000K	157 lm/W	14130 lm
OLE Dura ST120	120W	0.52A	10kg	400 x 565mm	<3500K	128 lm/W	15360 lm
					4000K	132 lm/W	15840 lm
					5000K	136 lm/W	16320 lm
					6000K	140 lm/W	16800 lm
OLE Dura ST150	150W	0.65A	13kg	400 x 725mm	<3500K	143 lm/W	21450 lm
					4000K	146 lm/W	21900 lm
					5000K	151 lm/W	22650 lm
					6000K	155 lm/W	23250 lm
OLE Dura ST180	180W	0.78A	13kg	400 x 725mm	<3500K	139 lm/W	25020 lm
					4000K	142 lm/W	25560 lm
					5000K	146 lm/W	26280 lm
					6000K	151 lm/W	27180 lm
OLE Dura ST 200	200W	0.87A	13kg	400 x 725mm	<3500K	138 lm/W	27600 lm
					4000K	141 lm/W	28200 lm
					5000K	145 lm/W	29000 lm
					6000K	150 lm/W	30000 lm
OLE Dura ST240	240W	1.04A	13.4kg	400 x 725mm	<3500K	122 lm/W	29280 lm
					4000K	125 lm/W	30000 lm
					5000K	128 lm/W	30720 lm
					6000K	132 lm/W	31680 lm
OLE Dura ST270	270W	1.17A	16.8kg	400 x 883mm	<3500K	133 lm/W	35910 lm
					4000K	135 lm/W	36450 lm
					5000K	138 lm/W	37260 lm
					6000K	143 lm/W	38610 lm
OLE Dura ST300	300W	1.30A	16.8kg	400 x 883mm	<3500K	133 lm/W	39900 lm
					4000K	135 lm/W	40500 lm
					5000K	138 lm/W	41400 lm
					6000K	143 lm/W	42900 lm

*Flux data based on Ta = 35°C. CCT & Lumen +/- 10%