

can provide 7-10 years warranty

# FLEXI ST



## FEATURES

- Input voltage: 220V~240V / Universal input
- Lumen Maintenance: L80 @ 50,000 hours
- Working Temperature: -25°C ~ 50°C
- Storage Temperature: -25°C ~ 80°C
- Power Factor: >0.95 at Full Load

## MATERIALS

- Casing material: Die-Cast Aluminum  
ADC12, Powder-Coated Finishing
- Cover: Tempered Glass
- Driver: Dimmable, Programmable  
& DALI Compatible 1~10V (Optional)



## Specification

Model No.	Power	Input current	Weight	Size	CCT	Efficacy	Lumen
OLE Flexi ST 70	70W	0.30A	7.0kg	320 x 562mm	<3500K	144 lm/W	10080 lm
					4000K	148 lm/W	10360 lm
					5000K	148 lm/W	10360 lm
					5700K	146 lm/W	10220 lm
OLE Flexi ST 75	75W	0.32A	7.8kg	320 x 562mm	<3500K	144 lm/W	10800 lm
					4000K	148 lm/W	11100 lm
					5000K	148 lm/W	11100 lm
					5700K	146 lm/W	10950 lm
OLE Flexi ST 90	90W	0.39A	7.8kg	320 x 562mm	<3500K	144 lm/W	12960 lm
					4000K	148 lm/W	13320 lm
					5000K	148 lm/W	13320 lm
					5700K	146 lm/W	13140 lm
OLE Flexi ST 120	120W	0.52A	8.0kg	320 x 562mm	<3500K	145 lm/W	17400 lm
					4000K	150 lm/W	18000 lm
					5000K	150 lm/W	18000 lm
					5700K	148 lm/W	17760 lm
OLE Flexi ST 150	150W	0.65A	8.0kg	320 x 562mm	<3500K	142 lm/W	21300 lm
					4000K	145 lm/W	21750 lm
					5000K	144 lm/W	21600 lm
					5700K	143 lm/W	21450 lm
OLE Flexi ST 180	180W	0.78A	8.0kg	320 x 562mm	<3500K	130 lm/W	23400 lm
					4000K	134 lm/W	24120 lm
					5000K	133 lm/W	23940 lm
					5700K	131 lm/W	23580 lm

\*Flux data based on  $T_a = 35^\circ\text{C}$ , CCT & Lumen  $\pm 10\%$